

Polymer Works, Hope Street  
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: [technical@advancedseals.co.uk](mailto:technical@advancedseals.co.uk)



<http://www.advancedseals.co.uk>

## Specification Sheet / 01 KT20A Hotmelt Transfer Tape



Certificate No. 11738-EMS-001  
ISO 9001:2015 ISO 14001:2015

Property	Value
Carrier	None
Release liner grade	Glassine
Release liner weight	80 gsm
Adhesive type	Hot Melt
Adhesive thickness	80 micron (not including foam)

Peel adhesion to steel	Loop tack	Release from liner	Temperature range
1000 n/m	700 n/m	10 n/m	-40 °c to 120 °c
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		

Change Control Date	Change
7/03/2014	Created



The above figures are average values.

We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

