Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555
f: 01384 252373
e: technical@advancedseals.co.uk

http://www.advancedseals.co.uk

Specification Sheet / 01
KT148 Double Sided Tissue Tape

8320
Certificate No. 11738-EMS-001
ISO 9001:2015 ISO 14001:2015

General description

This solvent acrylic adhesive combines high initial tack with good shear and peel results. The tissue base forms excellent cohesive strength. It has good resistance to UV, Plasticizer, Ageing and Moisture. Typical applications include laminating to foam and rubber for Automotive Industry.

Carrier

Description	*Grade*
Non-woven tissue	12 g/m²

Release Liner

Grade	*Colour*	*Weight*
P E Paper	White	110 g/m²

Adhesive

Type	*Grade*	*Thickness*
Solvent acrylic	High Performance	148 - 153 micron

Perfomance

Peel adhesion to steel	*Loop tack*	*Release from liner*	*Temperature range*
800 N/m	600 N/m	10 N/m	-10°C to 160°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		

Change Control Date	*Change*
20/07/2015	Created
12/01/2017	Adhesive thickness modified

The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (https://bit.ly/3nKm6Hj) unless otherwise stated.
Our standard terms and conditions of trading (https://bit.ly/3b3mThw) apply at all times.