

Polymer Works, Hope Street  
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: [technical@advancedseals.co.uk](mailto:technical@advancedseals.co.uk)



<http://www.advancedseals.co.uk>

# Specification Sheet (Superceded) / 01 A348fr Expanded PVC Foam Self adhesive Backed



Certificate No. 11738-EMS-001  
ISO 9001:2015 ISO 14001:2015

## Description

A medium density , easily compressible flame retardant foam PVC sealant with a strong acrylic pressure sensitive adhesive

## Key Features

Certified to Class B1 of DIN 4102 part 1

30% compression assures weathertight seal

Resists oxygen, Weather and fungi

Parameters	Units	Values	Norm
Density	kgs/m <sup>3</sup>	150	
Shore 00 Hardness		Shore 33	
Compression Waterseal		30%	
Force to Compress	N/cm <sup>2</sup>	3.4	
Compression Deflection	N/cm <sup>2</sup>	2.3	
Compression Set	Maximum	10%	
Water Absorption	Maximum	3%	
Minimum Application Temperature	°C	5	
Service Temperature Range	°C	-30 / +75	

Change Control Date	Change
30/9/15	Created



The above figures are average values.  
We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No W1007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

